

# TECHNICAL DATA SHEET



## MetoPrintEasy

**METO**<sup>®</sup>  
your retail label expert

EN

# MetoPrintEasy

Direct thermal printing



## Key features

- High quality double-walled clamshell design
- 152,4 mm per second (6") print speed
- 64 MB SDRAM and 128 MB Flash memory
- Easy media loading
- USB 2.0 Highspeed mode and other ports
- Versatile TSPL-EZD firmware emulates Eltron®, Zebra® and Datamax languages out of the box
- 2 years warranty
- ENERGY STAR® qualified
- Operation as stand-alone printer possible
- Production certified in accordance with ISO 9001 and ISO 14001

The Meto Print components – printer, templates and labels – are perfectly compatible and supplemented by an extensive retail service concept.

## Applications

- Retail
- Point of Sale (POS)
- Identification / Labelling of products
- Stock-taking & inventory control
- Document printing
- Labelling within healthcare application
- Logistics



## Technical data

<b>Material number</b>	30000885
<b>Resolution (dpi)</b>	203
<b>Printing method</b>	Direct Thermal
<b>Max. print speed</b>	152.4 mm/s (6")
<b>Max. print width</b>	108 mm (4.25")
<b>Max. print length</b>	25,400 mm (1000")
<b>Enclosure</b>	Double-walled plastic
<b>Dimension</b>	172 mm (W) x 165 mm (H) x 195 mm (D)
<b>Weight</b>	1,5 kg
<b>Label roll capacity</b>	127 mm (5") OD
<b>Processor</b>	32-bit RISC CPU
<b>Memory</b>	128 MB Flash memory / 64 MB SDRAM
<b>Interface</b>	RS-232 / USB 2.0 / Ethernet 10/100 Mbps / USB Host
<b>RTC (Real-Time-Clock)</b>	Real Time Clock
<b>Battery for RTC</b>	CR2032 (3V) Lithium
<b>External universal switching power supply</b>	Input: AC 100–240V, 50–60Hz / Output: DC 24V, 2,5A, 60W
<b>Operation switch, button, LED</b>	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)
<b>Sensors</b>	Transmissive gap sensor / Black mark reflective sensor / Head open sensor
<b>Internal fonts</b>	8 alpha-numeric bitmap fonts / Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
<b>Barcode (1D Barcode)</b>	Code 128 subsets A,B,C, Code128UCC, EAN128, Interleave 2 of 5, Code 39, Code 93, EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS
<b>Barcode (2D Barcode)</b>	CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)
<b>Font and barcode rotation</b>	0°, 90°, 180°, 270°
<b>Printer language</b>	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)
<b>Templates</b>	Maximum one print template may be utilized within printer
<b>Media type</b>	Continuous, black mark, fan-fold, notched (outside wound)
<b>Media width</b>	19 ~ 114 mm (0.7" ~ 4.5")
<b>Media thickness</b>	0.055 ~ 0.19 mm (2,16 ~ 7.48 mil)
<b>Media core diameter</b>	25.4 ~ 38 mm (1" ~ 1.5")
<b>Label length</b>	10 ~ 25,450 mm (0.39" ~ 1,000")
<b>Limited warranty</b>	Printer: 2 years / Print head: 25 km (1 million inches) or 12 months which comes first / Platen: 50 km (2 million inches) or 12 months which comes first
<b>Safety regulation</b>	CE Class B, TÜV / Safety, ENERGY STAR®
<b>Environmental concern</b>	Comply with RoHS, WEEE